



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01B 7/004, G01L 1/20, 5/22	A1	(11) International Publication Number: WO 97/40339
		(43) International Publication Date: 30 October 1997 (30.10.97)

(21) International Application Number: PCT/NL97/00202

(22) International Filing Date: 18 April 1997 (18.04.97)

(30) Priority Data:
1002907 19 April 1996 (19.04.96) NL(71) Applicant (for all designated States except US): TECHNISCHE
UNIVERSITEIT DELFT [NL/NL]; Julianalaan 134, NL-
2628 BL Delft (NL).

(72) Inventors; and


(75) Inventors/Applicants (for US only): ZEE, Fulco [NL/NL];
Anslostraat 7, NL-2533 KB Den Haag (NL). HOLWEG,
Eduardus, Gerardus, Maria [NL/NL]; Paradijspoort 44,
NL-2611 MB Delft (NL). REGTIEN, Paulus, Petrus,
Leonardus [NL/NL]; Julia Culpstraat 66, NL-7558 JB
Hengelo (NL). JONGKIND, Willem [NL/NL]; Drechtlaan
82, NL-2451 CN Leimuiden (NL).(74) Agent: VAN BREDA, Jacques; Octrooibureau Los en Stigter
B.V., Weteringschans 96, NL-1017 XS Amsterdam (NL).(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,
HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL,
PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA,
UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD,
SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD,
TG).

Published

With international search report.
In English translation (filed in Dutch).(54) Title: TACTILE SENSOR AND METHOD FOR DETERMINING A SHEAR FORCE AND SLIP WITH SUCH A TACTILE
SENSOR

(57) Abstract

The invention relates to a tactile sensor comprising a base plate provided at a first side with a plurality of electrically conducting wires forming a row, and provided at a second side opposite to the first side of the base plate with a plurality of electrically conducting wires forming a column, each of these wires forming cross points with the electrically conducting row wires. Each of the column wires forms an electrical contact with the row wires near each cross point, which electrical contacts are located at the first side of the base plate. The first side of the base plate is provided with a covering having a pressure-dependent electrical resistance and which, together with the electrical contact of the column wires and the row wires, is suitable to form one or more current paths. The covering is divided into segments, with each segment covering at least two adjacent cross points.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Tactile sensor and method for determining a shear force
and slip with such a tactile sensor

The invention relates to a tactile sensor comprising a base plate provided at a first side with a plurality of electrically conducting wires forming a row, and provided at a second side opposite to the first side
5 of the base plate with a plurality of electrically conducting wires forming a column, each of these wires forming cross points with the electrically conducting row wires, wherein each of the column wires forms an electrical contact with the row wires near each cross
10 point, which electrical contacts are located at the first side of the base plate, and the first side of the base plate is provided with a covering having a pressure-dependent electrical resistance and which, together with the electrical contacts of the column wires and the row
15 wires, is suitable to form one or more current paths.

Such a tactile sensor is known from the journal "De Ingenieur", volume 108, No. 5, 20 March 1996, pages 28-31. The base plate of the tactile sensor of the prior art is a so-called printed circuit board. Both sides of the print
20 are provided with this printed circuit. The printed circuit consists of 16 equidistant strips of conductive material on a first side of the print and 16 equidistant strips of electrically conducting material on the other side of the print arranged orthogonally to the first
25 strips. At the cross points, a metal connection from the one side to the other side is provided for the strips on the first side only, but in such a manner that these electric interconnections form islands at the cross points within the strips of conductive material on the other side
30 of the print. The latter side is also provided with a covering of an electrically conductive rubber which has a pressure-dependent electric resistance. By applying a load to the sensor on the side of the covering, it is possible to measure both the position and the force of the applied
35 load.

It is the objective of the invention to improve this known sensor such that this sensor can also measure tangential or shear forces and to enable the sensor to measure the start and progression of slip more accurately
5 and continuously.

To this end the tactile sensor according to the invention is characterized, in that the covering is divided into segments, each segment covering at least two adjacent cross points. This makes it possible to measure a
10 difference in load ensuing from shear forces at adjacent cross points because, in contrast with the prior art, the segmentation now admits varying normal forces at these adjacent cross points.

The invention also embodies a method for the deter-
15 mination of a shear force when a load is applied on a tactile sensor as discussed above. According to the invention this method is characterized in that the resistance values of current paths formed between the connection points of each of the electrically conductive row wires and of each
20 of the electrically conductive column wires is determined, that for each current path these resistance values are converted to numerical values which are a measure for the load at the cross points of the row and column wires, and that the difference between the numerical values of adjacent
25 cross points is determined, as being a measure of the shear force exerted on the sensor.

If the tactile sensor is made such that each segment covers four adjacent cross points forming the corners of a square, it is possible to measure the shear
30 forces occurring in the plane of the covering in any arbitrary orientation by resolving the measured forces in combining orthogonal directions determined by these four adjacent cross points.

A possible embodiment of the tactile sensor in
35 accordance with the invention is one in which the covering is composed of separate segments which are not interconnected. However, a preferred embodiment of the tactile sensor according to the invention is provided with a covering comprising an undivided base surface resting on

the first side of the base plate, while the base surface is provided with separate projections forming the segments. The manufacture of this tactile sensor is particularly simple. This covering can be particularly easily provided if it is formed from an electrically conducting rubber having a pressure-dependent electrical resistance, due to the fact that the rubber is incised crosswise, with the segments being located between the incisions.

As mentioned above, the tactile sensor according to the invention is particularly suitable for the measurement of shear forces. In addition, the invention provides a tactile sensor possessing an increased sensitivity for the determination of slip occurring while the tactile sensor is loaded. To this effect this sensor according to the invention is applied such that resistance values are determined of current paths formed between the connection points of each of the electrically conducting row wires and of each of the electrically conducting column wires, that these resistance values are converted for each current path to numerical values constituting a measure for the load at the cross points of the row and column wires, that these values are totalized to produce a principal value, and that from a series of these principal values a frequency spectrum is determined and the occurrence of predetermined frequency characteristics is detected as an indication of the slip.

The invention will now be further elucidated with reference to the drawing of a non-limiting embodiment. In the drawing

Fig 1a shows a top view of the tactile sensor according to the invention;

Fig. 1b shows a side view of the tactile sensor according to the invention;

Fig. 2a shows a cross-section of the tactile sensor according to the invention;

Fig. 2b shows a partial top view of the tactile sensor according to the invention;

Fig. 3 shows a resistance characteristic of the covering constituting part of the tactile sensor according to the invention;

Fig. 4a shows a measurement characteristic at normal load of the tactile sensor according to the invention; and

Fig. 4b shows a measurement characteristic when the tactile sensor according to the invention is loaded with a shear force.

Identical parts in the Figures carry identical reference numbers.

Fig. 1a shows the top view of the tactile sensor 1, wherein this top side of the material of the covering is incised. The covering is preferably formed from an electrically conducting rubber with a pressure-dependent electrical resistance of which a possible characteristic is shown in Fig. 3. The incisions are applied crosswise, with the segments 3 located between the incisions. This is also clearly visible in Fig. 1b, showing also that the covering, which is generally indicated by reference number 4, is applied on a base plate 5.

As can be more clearly seen in Fig. 2a, the base plate 5 is at both sides provided with a printed circuit, namely on the first side a printed circuit 6 and on the second side opposite the first side of the base plate 5, a printed circuit 7. The circuit 7 has metallized borings 8 and 9 through the material of the base plate 5 to allow electric contacts 10 and 11 to be formed at the first side of the base plate. A partial top view in which the covering 4 is not represented, is shown in Fig. 2b, representing a schematic top view of a part of the sensor, omitting the covering 4. At the under side of the base plate 5, electrically conducting wires 7 are shown as well as the contacts 10 and 11 provided at the top side of the base plate 5, electrically connected with the wires 7. These contacts 10 and 11 are arranged like islands in the electrically conducting wires 6 provided at the top side of the base plate 5, and are oriented transversely in relation to the conducting wires 7 at the under side of

the base plate 5. The electric contact between the contacts 10 and 11 which are connected with the conducting wires 7 and the conducting wires 6, is furnished by the covering 4. When this covering 4 is loaded, the electrical contact between the conducting wires 6 and the conducting wires 7 is enhanced and this is measured in order to determine the type and the load exerted on the tactile sensor 1.

As shown in Fig. 3, the resistance value R of the covering 4, which in this case is an electrically conducting rubber, decreases with increasing load. According to the invention the covering 4 is divided in segments 3, each segment covering at least two adjacent cross points. These cross points are the points where the electrical wires 7 and 6 cross. In the case shown in the present embodiment, these cross points coincide with the electrical contacts 10 and 11. In a preferred embodiment of the tactile sensor according to the invention, each segment 3 covers four adjacent cross points forming a square, so that the shear forces can be determined in two orthogonal directions.

Figs. 4a and 4b show an example of a tactile sensor according to the invention in which a row of 16 equidistant electrically conducting wires are provided at the under side of the base plate 5 and placed transversely to it, a column of 16 equidistant electrically conducting wires on the top side of the base plate 5, in which arrangement there are 256 cross points arrayed in a matrix. Fig. 4a shows the measuring results from normal loading of the tactile sensor according to the invention as measured along the 16 current paths of which one component is conducting wire 7. On the abscissa the cross points, numbered 1 to 16, are indicated, each of which is a component of such a current path. Fig. 4a shows that when applying an evenly distributed normal force F_n to the tactile sensor, an identical resistance value as plotted on the ordinate, is measured for each current path. If, as shown in Fig. 4b, apart from a normal force F_n also a shear force F_s is applied a measuring result as also shown in

this Figure, will ensue. It has been shown that each twosome of adjacent cross points located under a segment 3 provides a different resistance value. These resistance values are for each current path converted to numerical values, providing a measure of the load at these cross points. The difference between the adjacent cross points under one segment 3 as described above, is then determined as measure for the shear force F_s exerted on the sensor 1.

As already mentioned above, the tactile sensor according to the invention is also suitable for the determination of slip occurring while the sensor is loaded. To this effect resistance values are determined of current paths formed between the connection points of each of the electrically conducting row wires 6, and of each of the electrically conducting column wires 7, these resistance values are converted for each current path to numerical values constituting a measure for the load at the cross points of the row and column wires, these numerical values are totalized to produce a principal value, and from a series of these principal values a frequency spectrum is determined and the occurrence of predetermined frequency characteristics is detected as an indication of the slip.

CLAIMS

1. A tactile sensor comprising a base plate provided at a first side with a plurality of electrically conducting wires forming a row, and provided at a second side opposite to the first side of the base plate with a plurality of electrically conducting wires forming a column, each of these wires forming cross points with the electrically conducting row wires, wherein each of the column wires forms an electrical contact with the row wires near each cross point, which electrical contacts are located at the first side of the base plate, and the first side of the base plate is provided with a covering having a pressure-dependent electrical resistance and which, together with the electrical contacts of the column wires and the row wires, is suitable to form one or more current paths, characterized in that the covering is divided into segments, with each segment covering at least two adjacent cross points.

2. A tactile sensor in accordance with claim 1, characterized in that each segment covers four adjacent cross points forming the corners of a square.

3. A tactile sensor in accordance with claim 1 or 2, characterized in that the covering comprises an undivided base surface resting on the first side of the base plate, while the base surface is provided with separate projections forming the segments.

4. A tactile sensor in accordance with any of claims 1-3, wherein the covering is formed from an electrically conducting rubber having a pressure-dependent electrical resistance, characterized in that the rubber is incised crosswise, with the segments being located between the incisions.

5. A method for the determination of a shear force when a load is applied on a tactile sensor in accordance with any of claims 1-4, characterized in that the resistance values of current paths formed between the connection points of each of the electrically conductive row

wires and of each of the electrically conductive column wires is determined, in that for each current path these resistance values are converted in numerical values which are a measure for the load at the cross points of the row and column wires, and that the difference between the numerical values of adjacent cross points is determined, as being a measure of the shear force exerted on the sensor.

6. A method for the determination of slip occurring while a tactile sensor in accordance with any of the claims 1-4 is loaded, characterized in that resistance values are determined of current paths formed between the connection points of each of the electrically conducting row wires and of each of the electrically conducting column wires, that these resistance values are converted for each current path to numerical values constituting a measure for the load at the cross points of the row and column wires, that these values are totalized to produce a principal value, and that from a series of these principal values a frequency spectrum is determined and the occurrence of predetermined frequency characteristics is detected as an indication of the slip.




FIG 1A




FIG 1B




FIG 2A




FIG 2B




FIG 3




FIG 4A




FIG 4B

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/NL 97/00202

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G01B7/004 G01L1/20 G01L5/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01B G01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE INGENIEUR, vol. 108, no. 5, 20 March 1996, NETHERLANDS, pages 28-31, XP000614607 W.JONGKIND: "Robothand krijgt mens" cited in the application see the whole document ---	1-6
P,Y	WO 96 13704 A (BONNEVILLE SCIENT) 9 May 1996 see page 1, line 1 - page 5, line 5; figures 1,2,7D,11,12 see page 7, line 15 - page 10, line 18 see page 13, line 12 - line 30; claims 1,6,10,11 --- -/-	1-6

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

22 July 1997

Date of mailing of the international search report

30.07.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Brock, T

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/NL 97/00202

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PROCEEDINGS OF THE INSTRUMENTATION AND MEASUREMENT TECHNOLOGY CONFERENCE, ORVINE, CA., MAY 18 - 20, 1993, no. -, 18 May 1993, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 579-583, XP000400239 MCMATH W S ET AL: "HIGH SAMPLING RESOLUTION TACTILE SENSOR FOR OBJECT RECOGNITION" see the whole document ---	1,5,6
A	EP 0 658 753 A (HOME ROW INC) 21 June 1995 see the whole document ---	1,5,6
A	EP 0 595 532 A (AMERICAN TELEPHONE & TELEGRAPH) 4 May 1994 see the whole document ---	1,5,6
A	US 4 483 076 A (BROOKS WAHNER E) 20 November 1984 see the whole document ---	1,5,6
A	US 4 208 648 A (NAUMANN KARLHEINZ) 17 June 1980 see the whole document -----	1,5,6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 97/00202

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9613704 A	09-05-96	US 5553500 A	10-09-96
		US 5604314 A	18-02-97
		AU 4136196 A	23-05-96
EP 0658753 A	21-06-95	NONE	
EP 0595532 A	04-05-94	US 5313840 A	24-05-94
		JP 6258007 A	16-09-94
US 4483076 A	20-11-84	NONE	
US 4208648 A	17-06-80	DE 2737163 A	22-02-79
		JP 54033063 A	10-03-79